

FREEWAY PREMIUM P RN

5W-30 SAE 5W-30

MULTI-PURPOSE SYNTHETIC ENGINE OIL

APPLICATIONS

FREEWAY PREMIUM P RN 5W-30 is a multi-purpose SAE 5W-30 synthetic engine oil specially developed to meet both **Renault RN17** specifications required for certain Renault and Dacia gasoline and diesel engines from 2018 onwards, as well as **PSA B71 2290** specifications.

Thanks to its broad OEM compatibility, FREEWAY PREMIUM P RN 5W-30 simplifies maintenance and logistics operations while reducing the risk of product misapplication.

It is also suitable for gasoline and diesel engines requiring **ACEA C2** viscosity grade SAE 5W-30, including applications from manufacturers such as Fiat, Toyota, Iveco and others.

PERFORMANCE

Classifications:	ACEA C2-23 ACEA A5/B5-23	ACEA C3-23 API SQ	API SP
Specifications:	RN 0700 / 0710 MB 229.31 / 229.51 Fiat 9.55535-S3	PSA B 71 2290 MB 226.52	
Approvals:	Renault RN17	MB-Approval 229.52	

CUSTOMER BENEFITS

WEAR RESISTANCE • AFTER-TREATMENT SYSTEM PROTECTION

- Excellent oxidation resistance ensuring extended engine durability and service life.
- Meets Renault Long Life (LL) durability and wear test requirements.
- Low oil volatility helps reduce oil consumption during service life.
- Fully compatible with modern exhaust after-treatment systems such as DPF, GPF, SCR and NOx traps.

Warning: Some engines are not designed to use this type of lubricant. Always refer to the vehicle manufacturer's owner's manual before use.

 CHARACTERISTICS

	<i>Method</i>	<i>Units</i>	<i>Values</i>
<i>Density at 15°C</i>	-	-	0,852
<i>Viscosity at 40°C</i>	ASTM D445	mm²/s	73.7
<i>Viscosity at 100°C</i>	ASTM D445	mm²/s	12.3
<i>Viscosity index</i>	ASTM D2270	-	165
<i>TBN</i>	ASTM D2896	mgKOH/g	8.5
<i>Flash point</i>	ASTM D93	°C	237
<i>Pour point</i>	ASTM D97	°C	-45

The values shown above are typical values provided for guidance only.

 RECOMMENDATION**Shelf Life**

36 months when stored in the original, tightly sealed packaging under normal storage conditions.

Storage Conditions

Store at ambient temperature in a clean, dry environment, protected from water, dust and humidity. Do not store above **40°C**. Avoid exposure to direct sunlight, severe cold or significant temperature fluctuations.

 HEALTH, SAFETY AND ENVIRONMENT

Health and safety information for this product is provided in the **Safety Data Sheet (SDS)**, available upon request and on www.hafa.fr.

This product must not be used for any purposes other than those for which it is intended.

After use, dispose of the product in accordance with local environmental regulations.