

FREEWAY INITIAL ***A3/B4 5W-40*** SAE 5W-40

SYNTHETIC ENGINE OIL FOR PASSENGER VEHICLES

APPLICATIONS

FREEWAY INITIAL A3/B4 5W-40 is a synthetic lubricant specially formulated for gasoline engines (multi-valve, turbocharged with or without catalytic converter) and naturally aspirated or turbocharged diesel engines in passenger cars and light commercial vehicles not equipped with particulate filters.

Its advanced additive package makes it suitable for both urban and highway driving, all driving styles, and all seasons. Due to its compliance with multiple manufacturer specifications, FREEWAY INITIAL A3/B4 5W-40 is a versatile product.

FIAT performance levels 9.55535-H2, M2, and N2 require the lubricant to meet both ACEA A3/B4 and 5W-40 specifications.

PERFORMANCE

Classifications : ACEA A3/B4-23
API SN

Specifications : MB 229.3
VW 502 00 / 505 00
RN 0700 / 0710

MB 229.5
Porsche A 40
PSA B71 2296-18

CUSTOMER BENEFITS

ANTI-WEAR PROTECTION • ENGINE PROTECTION

- Immediate lubrication of engine components at cold start, resulting in increased engine longevity.
- Maximum lubricating and thermal performance due to advanced additives, ensuring absolute operational safety.
- Detergent, dispersant, anti-wear, antioxidant, and anti-corrosion properties that prevent engine wear and deposit formation.

Warning: Some engines are not designed for the use of this type of lubricant. Always consult the vehicle's maintenance manual.

CHARACTERISTICS

	Method	Units	Values
Density at 15°C	-	-	0.87
Viscosity at 100°C	ASTM D445	mm ² /s	14.41
Viscosity at 40°C	ASTM D445	mm ² /s	87.3
Viscosity Index	ASTM D2270	-	172
Flash Point	ISO 2719	°C	>200

The values of the properties shown in this table are typical and provided for information purposes only.

RECOMMENDATIONS

Shelf life : 36 months in tightly sealed containers under normal storage conditions.

Storage conditions : Store at ambient temperature, protected from water, dust, and humidity. Do not store above 40°C or expose to strong sunlight, extreme cold, or large temperature fluctuations.

HEALTH, SAFETY AND ENVIRONNEMENT

Health and safety recommendations for this product are provided in the Safety Data Sheet (SDS), available on request and at www.hafa.fr.

This product must only be used for its intended purpose. For disposal, follow environmental regulations.