

FREEWAY GEAR ATF CVT

SYNTHETIC CONTINUOUSLY VARIABLE TRANSMISSION FLUID (CVT)

APPLICATIONS

FREEWAY GEAR ATF CVT is a high-performance synthetic transmission fluid specifically developed for chain- and belt-driven Continuously Variable Transmissions (CVTs).

It is particularly recommended for CVTs fitted to vehicles manufactured by leading American OEMs such as GM, Ford and Dodge, Asian manufacturers including Honda, Hyundai, Kia, Mazda, Mitsubishi and Subaru, as well as European brands such as Audi, BMW and Mercedes-Benz.

Thanks to its broad compatibility with numerous OEM specifications, FREEWAY GEAR ATF CVT is suitable for the majority of CVT applications.

PERFORMANCE

Specifications: Meets the requirements of numerous OEM specifications (see compatibility list on page 2).

CUSTOMER BENEFITS

TRANSMISSION DURABILITY • DRIVING COMFORT

- Outstanding wear protection, even under severe operating conditions, meeting the demanding requirements of modern CVT transmissions.
- Minimizes metal-to-metal friction between belts or chains and pulleys through advanced friction modifier technology.
- Provides smooth and consistent driving performance by maintaining stable friction characteristics throughout the service life.
- Low-viscosity formulation contributes to improved fuel efficiency and reduced power losses.
- Extended transmission life through excellent thermal stability, strong oxidation resistance and durable lubricating film at high operating temperatures.

Important: *FREEWAY GEAR ATF CVT is not suitable for CVT transmissions fitted to hybrid vehicles.*

CHARACTERISTICS

	Method	Units	Values
Colour	Visual	-	Amber
Kinematic Viscosity at 100°C	ASTM D445	mm ² /s	7.0
Kinematic Viscosity at 40°C	ASTM D445	mm ² /s	34.3
Viscosity Index	ASTM D2270	-	171
Density at 15°C	-	-	0.845
Brookfield Viscosity at -40°C	-	mPa.s	17685
Flash Point	ISO 2592	°C	>180

The values shown above are typical values provided for guidance only.

Version of 01/09/2025

<i>FREEWAY GEAR ATF CVT is suitable for applications where one of the following OEM specifications or fluids is specified:</i>	
Audi	G 052 180, G 052 516
BMW,Mini	EZL 799, 799A
Daihatsu	Ammix CVTF-DC, Ammix CVTF-DFE
Dodge/Jeep	Mopar CVTF +4
Ford (GFT & Getrag)	M2C-928A (CFT-23), M2C933-A (CFT-30)
GM	DEX-CVT, GM CVT
Hyundai/Kia	SP-CVT1
Honda	HMMF, HCF-2
Mazda	CVTF 3320
Mercedes-Benz	MB 236.20
Mitsubishi	Diaqueen CVTF J1, CVTF J4
Nissan	NS-1, NS-2, NS-3
Subaru	E-CVT, Lineartronic CVTF-II, Lineartronic CV-30, High Torque CVTF
Suzuki	CVTF Fluid Green 1, Fluid Green 2, CVTF 3320
Toyota/Lexus	TC, FE, WS (Prius eCVT only)
Volkswagen	TL 052 180, TL 052 516

RECOMMENDATION

Shelf Life

36 months when stored in the original, tightly sealed packaging under normal storage conditions.

Storage Conditions

Store indoors at ambient temperature in a clean, dry environment, protected from water, dust and moisture.

Storage temperatures should not exceed **50°C**. Avoid exposure to direct sunlight, severe frost or excessive temperature fluctuations.

HEALTH, SAFETY AND ENVIRONMENT

Health and safety information for this product is available in the **Safety Data Sheet (SDS)**, which can be obtained upon request or downloaded from www.hafa.fr.

This product should only be used for its intended applications.

Dispose of used product in accordance with local environmental regulations.