

FREEWAY GEAR ATF FULL

MULTI-VEHICLE FULLY SYNTHETIC AUTOMATIC TRANSMISSION FLUID

APPLICATIONS

FREEWAY GEAR ATF FULL is a fully synthetic fluid specially developed for modern automatic transmissions. Its compatibility with a wide range of OEM specifications makes it suitable for numerous automatic transmissions and torque converters used in passenger cars, SUVs and off-road vehicles. FREEWAY GEAR ATF FULL is also suitable for power steering systems, marine reverse gears, hydrostatic transmissions and hydraulic or mechanical systems whenever the specifications listed below are required.

AVANTAGES CLIENTS

ANTI-FRICTION PERFORMANCE • FUEL ECONOMY

- Stable friction characteristics throughout the service life ensure smooth, fast and vibration-free gear shifting.
- Outstanding protection for increasingly compact, highly loaded transmission gear sets.
- Enhanced oxidation resistance supports the extended drain intervals recommended by vehicle manufacturers.
- Fuel-saving properties, particularly during cold-start operation.
- Fully compatible with seals and materials used in modern transmission systems.

Warning: FREEWAY GEAR ATF FULL must not be used in CVT (Continuously Variable Transmission) or DCT (Dual Clutch Transmission) applications, nor where Allison TES-295 or Allison TES-389 fluids are specified.

Some transmissions are not designed for this type of lubricant. Always refer to the vehicle manufacturer's owner's manual before use.

CHARACTERISTICS

	Method	Units	Values
Density at 15°C	-	-	0.849
Viscosity at 100°C	ASTM D445	mm ² /s	6.2
Viscosity at 40°C	ASTM D445	mm ² /s	31.5
Brookfield Viscosity at -40°C	-	mPa.s	13680
Viscosity index	ASTM D2270	-	150

The values shown above are typical values provided for guidance only.

PERFORMANCE

FREEWAY GEAR ATF FULL is suitable for applications where the vehicle manufacturer specifies one of the following fluids or specifications:	
ATF	Esso LT 71141, JWS3309, Texaco ETL7045E, ETL 8072B, Mobil ATF 3309
ATF Shell	Shell 3353, 134, 3403-M115, M-1375.4, LA 2634, L12108
Allison	C4
Bentley	P/N PY112995PA
BMW / MINI	ATF-3+ ,P/N 81 22 9 400 272/275 ,P/N 81 22 9 407 858/859 , P/N 83 22 0 024 249/359 , P/N 83 22 0 026 922 , P/N 83 22 0 142 516, P/N 93 22 0 397 114, P/N 83 22 0 402 413 , P/N 83 22 0 403 248,P/N 83 22 0 403 249, P/N 83 22 2 152 426, P/N 83 22 2 289 720, P/N 83 22 2 163 514, P/N 83 22 2 355 599, P/N 83 22 2 305 397, P/N 83 22 7 542 290, P/N 83 22 9 407 765, P/N 83 22 9 407 807
FCA	ATF+, +2, +3, +4, P/N 05127382AA, P/N 68043742AA, P/N 68157995AA, SP-III, SP 4, Fiat 9.55550-AV1, Fiat 9.55550-AV2, Fiat 9.55550-AV4, Fiat 9.55550-AV5, Fiat 9.55550-AV6
Ford / Lincoln / Mercury	Mercon ULV, XT-10-QLV (LV), XT-6-QSP (SP) , XT-2-QDX (M) ,XT-2-QSM (Syn),XT-5-QM (V), XT-8-QAW (premium), XT-9-QMM5 (FRN5) , WSS M2C 922 A1,
GM	AW1 , DEXRON II , IID , IIE , IIIG ,IIIH , VI ,P/N 12378515 (synthetic), P/N 88863400 , P/N 88863401 , P/N 19 40 700 , P/N 19 40 767 , P/N 21005966 , P/N 22717466 , P/N 88900925 , P/N 9986195 , Saturn T-IV , TASA, Dexron ULV, Dex HP
Honda / Acura	DW-1, Z-1, ATF Type 3.0, ATF Type 3.1
Hyundai/Kia	ATF Red-1K, Genuine ATF, JWS-3309 T-4, NWS-9638 T-5, P/N 040000C950SG, P/N UM040 CH20 Red-1, SP-IV, SPH-IV, SP-IV-RR, SP-III, SP-II,
Isuzu	Besco ATF-II , Besco ATF-III, Genuine ATF , P/N 08200-9001, SCS, ATF WSI
Jaguar	JLM20238 , JLM21044 , JLM 20292 , Fluid 8432 , K17, WSS-M2C922-A1
JASO	M315-2013 1A-LV
Land Rover	Texaco N402, P/N TYK5000050 , P/N LR0022460 : LV, STC 4863
MAN	MAN 339A, 339D, 339F
Maserati	P/N 231603
Mazda	M-III ,M-5, FZ, F-1 ,JWS3317, Type T-IV, ATF-S1,ATF-N1
Mercedes Benz	MB 236.17, MB 236.10, MB 236.11, MB 236.12, MB 236.14, MB 236.15, MB 236.41, MB 236.5
Mitsubishi	Diaqueen ATF PA, SP, SP-II, SP-III, ATF-J2, ATF-J3 , P/N MS991156
Nissan / Infinity	402, Matic fluid D, J, K, P, S, R, W, Fluid A
Peugeot / Citroen	P/N Z 000169756, PSA 1635056080
Porsche	P/N 000 043 205 09, P/N 999 917 547 00 (A2), P/N 000 043 205 28, P/N 000 043 204 41, P/N 000 043 304 00, P/N 000 043 204 63
Renault	Matic D2, SATF-D, DP-0
Saab	JWS 3309, P/N 93 165 147, ATF HP
Ssang Yong	DSIH 5M-66, DSIH 5M-52
Subaru	HP, P/N K0140Y0700, ATF-WS
Suzuki	ATF 3314, ATF 3317, ATF 2326, ATF 5D06
Toyota / Lexus / Scion	Scion FZ, Type D-II, Type T, Type T-II, Type T-III, Type T-IV, Type WS (JWS 3324)
Volvo	P/N 1161521, PN 1161540/1161640, P/N 1161621
VW	G 052 025 A2, G 052 162(-A1, -A2), G 052 990(A2), G 055 005 -A2,-, G 055 025 (A2), G 055 162 (A2 , A6), G 055 540 (A2), G 060 162 (A2), GUS 000 162
ZF	ZF Lifeguardfluid 6, ZF Lifeguardfluid 8, ZF Lifeguardfluid 9, ZF TE-ML 11A, ZF TE ML-11B, ZF Lifeguard Hybrid 1

 RECOMMENDATION

Warning: Some transmissions are not designed for this type of lubricant. Always consult the vehicle manufacturer's owner's manual before use.

Shelf Life

36 months when stored in the original, tightly sealed packaging under normal storage conditions.

Storage Conditions

Store at ambient temperature in a clean, dry environment, protected from water and moisture.

Do not store above **35°C**. Avoid exposure to direct sunlight, severe cold or significant temperature fluctuations.

 HEALTH, SAFETY AND ENVIRONMENT

Health and safety information for this product is available in the **Safety Data Sheet (SDS)**, available upon request or at www.hafa.fr.

This product must not be used for purposes other than those for which it is intended.

Dispose of used product in accordance with applicable local environmental regulations.