

FREEWAY RACING 5W-50

SAE 5W-50

FULLY SYNTHETIC LUBRICANT FOR HIGH-PERFORMANCE ENGINES AND HYDROSTATIC TRANSMISSIONS

APPLICATIONS

FREEWAY RACING 5W-50 has been specifically developed for high-output, high-performance engines operating under severe conditions, both on the road and on the track.

FREEWAY RACING 5W-50 provides outstanding engine protection, ensuring exceptional reliability in racing applications while maintaining optimum engine performance under prolonged high-load operating conditions.

FREEWAY RACING 5W-50 is specially formulated for heavily loaded racing engines operating over a wide range of temperatures and engine speeds.

FREEWAY RACING 5W-50 is also ideally suited for the lubrication of hydrostatic transmissions used in lawn and garden equipment fitted with Tuff Torq-type gearboxes requiring an SAE 5W-50 lubricant meeting ACEA A3/B4 performance level.

PERFORMANCE

Specifications: ACEA A3/B4-23

API SP

CUSTOMER BENEFITS

OPTIMUM PROTECTION • MAINTAINED MECHANICAL PERFORMANCE

- Excellent lubrication performance at both low and high operating temperatures, providing outstanding protection for moving engine components.
- Helps maintain the cleanliness of critical engine parts through advanced detergent and dispersant additive technology.
- SAE 5W-50 viscosity grade ensures stable oil pressure under high-temperature operating conditions.
- Provides optimum protection of mechanical components thanks to excellent resistance to high temperatures and oxidation.

CHARACTERISTICS

	<i>Method</i>	<i>Units</i>	<i>Values</i>
Density at 15°C	-	-	0,85
Viscosity at 100°C	ASTM D445	mm²/s	19,07
Viscosity at 40°C	ASTM D445	mm²/s	116
Viscosity index	ASTM D2270	-	186
CCS at -30°C	ASTM D5293	cP	5053
Flash point	ISO 2719	°C	205

The values shown above are typical characteristics and are provided for guidance only.

 RECOMMENDATIONS

Caution: *Some engines are not designed for use with this type of lubricant. Always refer to the vehicle manufacturer's owner's manual before use.*

Shelf Life: 36 months when stored in tightly sealed original containers under normal storage conditions.

Storage Conditions: Store at ambient temperature in a dry place, protected from water and moisture. Products should not be stored at temperatures above 35°C (95°F) and should be protected from direct sunlight, severe cold, and significant temperature fluctuations.

 HEALTH, SAFETY AND ENVIRONMENT

Health and safety recommendations for this product are provided in the Safety Data Sheet (SDS), available upon request and on the manufacturer's website.

This product should only be used for its intended purpose. Dispose of used product responsibly and in accordance with local environmental regulations.