HAFA

TECHNICAL DATA SHEET

FREEWAY RACING 10W-60

SAE 10W-60

FULLY SYNTHETIC ENGINE OIL FOR SPORT AND HIGH-PERFORMANCE USE

APPLICATIONS

FREEWAY RACING 10W-60 is specifically developed for high-performance, heavily stressed engines used both on the road and in racing conditions.
It provides outstanding protection to ensure exceptional reliability in motorsport applications and maintains engine performance under prolonged high-load conditions.
FREEWAY RACING 10W-60 is designed for racing engines operating under severe stress across a wide range of temperatures and engine speeds.

PERFORMANCE

High-performance synthetic lubricant meeting the following standards:
Classification: ACEA A3/B4-12 API SL/CF

CUSTOMER BENEFITS

OPTIMUM PROTECTION • MAINTAINED ENGINE PERFORMANCE

- Excellent lubrication of engine components at both low and high temperatures, ensuring superior protection of moving mechanical parts.
- Keeps engine components clean thanks to its advanced detergent and dispersant additive package.
- Maximizes power output and reduces operating temperatures through reinforced friction modifier technology.
- Low Noack volatility helps reduce oil consumption.
- High viscosity grade ensures stable oil pressure at elevated operating temperatures.

CHARACTERISTICS

	Method	Units	Values
Density at 15°C	-	-	*0.857*
Viscosity at 100°C	*ASTM D445*	*mm²/s*	*23.6*
Viscosity at 40°C	*ASTM D445*	*mm²/s*	*172.6*
Viscosity index	*ASTM D2270*	-	*167*
Noack Volatility	*ASTM D5800*	*%*	*6.3*

The values shown above are typical values provided for guidance only.

Version of 22/11/17