

FREEWAY INITIAL GF-6 0W-20

SAE 0W-20

ENERGY-SAVING SYNTHETIC LUBRICANT FOR PETROL OR HYBRID VEHICLE ENGINES

APPLICATIONS

FREEWAY INITIAL GF-6 0W-20 has been specially developed to suit very recent downsized petrol engines, STOP & START systems and hybrid engines which require a low viscosity lubricant. FREEWAY INITIAL GF-6 0W-20, with its SAE 0W-20 viscosity, reduces the hydrodynamic friction of the oil as much as possible, extracting all the power from the engine and saving on fuel consumption. FREEWAY INITIAL GF-6 0W-20 meets the specific needs of HEV and PHEV (Plug-in Hybrid) hybrid electric vehicles, and is particularly recommended for new hybrid and petrol engines from brands such as Toyota, Hyundai, Suzuki, Subaru, Kia, Lexus...

PERFORMANCES

Classifications: ILSAC GF-6 A

API SP-RC

Specifications: GM Dexos 1 Gen 3

BENEFITS

ENERGY SAVING

MOTOR PROTECTION

- Maximum engine protection against wear and fouling.
- Improved performance even at low temperatures, allowing oil pressure to be built up instantaneously, thereby extending engine life.
- Significant improvement in fuel economy thanks to its exceptionally low viscosity.
- Meets the LSPI requirement for low-speed pre-ignition.
- Protection against timing chain wear.

Warning: some engines are not designed to use this type of lubricant. Always consult the vehicle maintenance booklet.

CHARACTERISTICS

	Method	Units	Values
Relative density @ 15°C	-	-	0.845
Viscosity @ 100°C	ASTM D445	mm ² /s	9.0
Viscosity @ 40°C	ASTM D445	mm ² /s	47.6
Viscosity index	ASTM D2270	-	173
TBN	ASTM D2896	mgKOH/g	7.0

The values of the characteristics shown in this table are typical values given as an indication

 **ADVICE**

Product lifetime: 36 months in hermetically sealed packages and under normal storage conditions.

Storage conditions: It is recommended to store the products at room temperature away from water, dust, and moisture. The products should not be stored at temperatures above 50°C and should not be exposed to strong sunlight, intense cold or strong temperature fluctuations.

 **HEALTH, SAFETY AND ENVIRONMENT**

The health and safety recommendations for this product can be found in the Material Safety Data Sheet (MSDS). It is available on request and at www.hafa.fr.

This product must not be used for any purpose other than its intended use. When disposing of the product after use, please consider the environment and observe local regulations.