

FREEWAY PREMIUM C3 5W-40

EUROMAX

SAE 5W-40

HIGH PERFORMANCE SYNTHETIC LUBRICANT

APPLICATIONS

FREEWAY PREMIUM C3 5W-40 is a high performance lubricant specially designed for the latest generation of cars equipped with direct injection petrol and turbo diesel engines. FREEWAY PREMIUM C3 5W-40 is intended for vehicles equipped with or without particulate filters or three-way catalysts when a 5W30 grade oil is not required by the manufacturer, such as certain KIA, DACIA, NISSAN, SUZUKI, HYUNDAI engines. The FIAT 9.55535-S2 performance level requires the lubricant to be both ACEA C3 and 5W-40.

PERFORMANCES

Classification:	ACEA C3-12 API SN / CF	
Specifications:	MB 229.31 FORD WSS-M2C917A GM DEXOS 2 FIAT 9.55535-S2	BMW LL-04 PORSCHE A40 MB 226.5
Approvals:	VW 502 00/505 01	RN0700 / 0710

CUSTOMER BENEFITS

ENHANCED RESISTANCE • REDUCED POLLUTANT RATES

- Enhanced shear resistance to maintain engine performance.
- Low polluting emissions rate due to its formulation with reduced content in sulphated ash, phosphorus and sulfur.
- Compatibility with modern post processing systems.

Caution: some engines are not designed to use this type of lubricant. Always refer to the vehicle maintenance manual.

CHARACTERISTICS

	<i>Method</i>	<i>Units</i>	<i>Values</i>
<i>Density at 15 °C</i>	-	-	0.855
<i>Viscosity at 100 °C</i>	ASTM D445	mm ² /s	14.0
<i>Viscosity at 40 °C</i>	ASTM D445	mm ² /s	84.4
<i>Viscosity index</i>	ASTM D2270	-	171
<i>Flash point</i>	ISO 2719	°C	209

The values of the characteristics in this table are typical values given as an indication only.